

RigidLock Plus

∂ SPECIFICATIONS

Style Number: Plank Size: Product Construction: Wear Layer: Edge: Embossing: Installation Method: Recycled Content: Certifications:	RP415203 7.01" x 47.91" x 6.5 mm 5.5 mm Rigidcore + 1 mm MaxStepPr 20 mil with MaxProtect® Coating ColorEdge® Embossed in Register Floating None GreenGuard Gold®	OTM
Classification Chemical Resistance Critical Radiant Flux Dimensional Stability Residual Indentation Resistance to Heat Resistance to Light Smoke Density Thickness Static Load Limit Delta IIC Impact Insulation Sound Transmission	(ASTM F1700-04) (ASTM F 925) (ASTM E 648-06) (ASTM F 2199) (ASTM F 1914) (ASTM F 1514) (ASTM F 1515) (ASTM E 662) (ASTM F 387) (ASTM F 970) (ASTM E2197-2003) (ASTM E492-09) (ASTM E90-2009)	Class III, Type B Passes Passes Passes Passes Passes Passes Passes Passes TBD IIC 66 TBD

PACKAGING

Square Feet Per Carton:	23.32	Pieces Per Carton:	10	
Square Feet Per Pallet:	1,632.40	Cartons Per Pallet:	70	
Square Feet Per Container:	32,648	Pallets Per Container:	20	
Weight Per Carton:	36.50 lbs	Weight Per Pallet:	2,555 lbs	

ê COLOR LINE

e WARRANTIES

Lifetime Limited Waterproof^{*}

Lifetime Limited Residential^{*}

10 Year Limited Commercial*

*Please visit our website for full warranty details.